



Specifications:

1. Rated Voltage :125V AC/DC
2. Rated Current :1A AC,DC
3. Withstand Voltage :200V AC/minute
4. Contact Resistance:50m $\Omega$  (MAX.)
5. Insulation Resistance:100m $\Omega$  (MIN.)
6. Storage Temperature Range:−40°C~+85°C;
7. Operation Temperature Range:−25°C~+70°C;

③	端子	黄铜H65	镀亮锡	7PCS
②	固定片	黄铜H65	镀亮锡	2PCS
①	塑胶主体	LCP	本色	1PCS
序号	配件名称	材质	电镀 颜色	数量



深圳市华宇创精密电子有限公司

TOLERANCE: X.X $\pm 0.30$ X.XX $\pm 0.25$ X.XXX $\pm 0.15$ X: $\pm 2^\circ$ X.X: $\pm 0.5^\circ$	DRAWED BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 1.25PH 立式贴片WAFER
CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC285-LFN-125	MOLD NO.
APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO. HYC-2507111224	SHEET NO. 1 OF 1