








电器原理图



技术参数

Technical Specification:

安装孔径 Mounting hole size: 19mm

开关组合 Switch combination: 1NO

头部形状 Head type: 平头 Flat round head

操作类型 Operation type: 自复式 Momentary

开关额定值 Switch rating: 20mA/36VDC

防水等级 Protection level: IP67,IK08

工作环境温度 Ambient temperature: -20~+55

动作行程 Operation stroke: ≤2mm

动作力 Operation pressure: ≤4N

连接形式 Tail Configuration: 接线插片

Connection terminal

拧紧力矩 Nut torque: 5~14Nm

外观材料 Enclosure material: 黄铜镀镍/不锈钢

Nickel plated brass/stainless steel

接触电阻 Contact resistance: ≤50mΩ

绝缘电阻 Insulation resistance: ≥1000mΩ

机械寿命 Mechanical life: 1,000,000 cycles

电气寿命 Electrical life: 50,000 cycles

带灯类型 Led type: 环形灯 Ring led illuminated

灯色 Led color: R, O, Y, B, W, G, P

电压 Led voltage: 2v/3v/6v/12v/24v/110v/220v

灯泡寿命 Led life: 40,000hours



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2" X.X' ±0.5"	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 金属按钮开关 无锁平头	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC-D2214NP-XX	MOLD NO.
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2510211624	SHEET NO. 1 OF 1