





Circuits	Dimensions(mm)				Circuits	Dimensions(mm)			
	A	B	C	D		A	B	C	D
02	1.00	4.80	3.10	2.50	17	16.00	19.80	18.10	17.50
03	2.00	5.80	4.10	3.50	18	17.00	20.80	19.10	18.50
04	3.00	6.80	5.10	4.50	19	18.00	21.80	20.10	19.50
05	4.00	7.80	6.10	5.50	20	19.00	22.80	21.10	20.50
06	5.00	8.80	7.10	6.50	21	20.00	23.80	22.10	21.50
07	6.00	9.80	8.10	7.50	22	21.00	24.80	23.10	22.50
08	7.00	10.80	9.10	8.50	23	22.00	25.80	24.10	23.50
09	8.00	11.80	10.10	9.50	24	23.00	26.80	25.10	24.50
10	9.00	12.80	11.10	10.50	25	24.00	27.80	26.10	25.50
11	10.00	13.80	12.10	11.50	26	25.00	28.80	27.10	26.50
12	11.00	14.80	13.10	12.50	27	26.00	29.80	28.10	27.50
13	12.00	15.80	14.10	13.50	28	27.00	30.80	29.10	28.50
14	13.00	16.80	15.10	14.50	29	28.00	31.80	30.10	29.50
15	14.00	17.80	16.10	15.50	30	29.00	32.80	31.10	30.50
16	15.00	18.80	17.10	16.50					

Specifications:

Contact resistance: $\leq 20\text{m}\Omega$

Insulation resistance: $\geq 100\text{M}\Omega$

Rated voltage: 50V AC DC

Rated current: 1.0A AC DC

Withstand Voltage: 500V AC/minute

Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Housing: PA6T UL94V-0, Natural

Contacts: Phosphor bronze/Matte Sn

Solder Tabs: Phosphor bronze/Matte Sn



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ± 0.30

X.XX ± 0.25

X.XXX ± 0.15

X' $\pm 2^{\circ}$ X.X' $\pm 0.5^{\circ}$



UNIT: mm [inch]

SCALE: 1:1

SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

1.0PH 1.85H 卧贴WAFER

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC216-WFN-100

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2209021638

SHEET NO.

1 OF 1