


A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	



1. 材料

A. 主体: LCP, 黑色, 白色, UL 94-V0;

B. 端子: C2680H65, 电镀刷金;

C. 外壳: 不锈钢, 镀全镍;

2. 主要特性

A. 电压等级: 20V AC;

B. 电流: 3A;

C. 工作温度: -40° c~85° c;

3. 电气要求:

A. 接触电阻: 40mΩ Max, (初始), 50mΩ Max. (最后);

B. 电压: 100V AC 1分钟;

C. 绝缘电阻: 100MΩ min. DC 500v;

4. 机械性能:

A. 插入力: 5~20N. (从1~10,000次);

B. 拔出力: 8~20N. (从1~1,000次);

6~20N. (从1,001~10,000次);

C. 耐久性寿命: 3,000次;



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

X' ±2° X.X' ±0.5°

UNIT: mm [inch]

SCALE: 1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

CHECKED BY :

马跃

DATE :

2014-02-23

APPROVED BY :

邱敏

DATE :

2014-02-23

PART NAME:

USB TYPE C 母座16P 四脚插板2.0脚 有柱

PART NO.

HYC388-USBC16-200

MOLD NO.

DRAW NO:

HYC-2212061150

SHEET NO.

1 OF 1