




NOTES:

1.MECHANICAL:

MATING FORCE: 35N MAX.

UNMATING FORCE: 10N MIN,INITIAL.

8~20N AFTER 10000 CYCLES.

DURABILITY: 5000 CYCLES MIN.

2.ELECTRICAL:

CURRENT: 1.0A

VOLTAGE: 30V MAX

WITHSTANDING VOLTAGE: 100V AC

CONTACT RESISTANCE: 30 m Ω MAX INITIAL;40 m Ω MAX AFTER 10000 CYCLES

3.ENVIRONMENTAL

OPERATING TEMPERATURE RANGE $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$

4. SALT SPRAY : 24 H AT 35%DC WITH

5%-SALT-SOLUTION CONCENTRATION.

5.PRODUCT SPEC:SP-MICRO USB-001

6.PACKAGE SPEC:DWG-PK MUB-0XX

7.PRODUCT MEET FOR ROHS STANDARD



深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X' $\pm 2^{\circ}$ X.X' $\pm 0.5^{\circ}$

UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

MICRO USB 3.0 四脚沉板

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC10-USBD10-075

MOLD NO.

DRAW NO: HYC-USB16070410

APPROVED BY:

邱国夷

DATE :

2014-02-23

SHEET NO.

1 OF 1

The following part fittings of a machine

PART NO.	PART NAME	Q'TY	Material
	Housing	1	LCP 130i 黑色
	Terminal	10	C5191R-H,T=0.15mm:
	shell	1	SUS304-1/2H,T=0.30mm