


RECOMMEND PCB LAYOUT(TOP VIEW)
GENERAL TOLERANCE ± 0.05

NOTES:

1.MECHANICAL:

MATING FORCE: 35N MAX.

UNMATING FORCE: 10N MIN,INITIAL.

8~20N AFTER 10000 CYCLES.

DURABILITY: 5000 CYCLES MIN.

2.ELECTRICAL:

CURRENT: 1.0A

VOLTAGE: 30V MAX

WITHSTANDING VOLTAGE: 100V AC

CONTACT RESISTANCE: 30 m Ω MAX INITIAL;

40 m Ω MAX AFTER 10000 CYCLES

3.ENVIRONMENTAL

OPERATING TEMPERATURE RANGE $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$

4. SALT SPRAY : 24 H AT 35%DC WITH
5%-SALT-SOLUTION CONCENTRATION.

5.PRODUCT SPEC:SP-MICRO USB-001

6.PACKAGE SPEC:DWG-PK MUB-OXX

7.PRODUCT MEET FOR ROHS STANDARD

The following part fittings of a machine			
PART NAME	Q'TY	Material	
Housing	1	LCP 130i	黑色
Terminal	10	C5191R-H,T=0.15mm:	
shell	1	SUS304-1/2H,T=0.30mm	

DESCRIPTION	DIM A
MICRO USB 3.0 DIP(12.55MM)+2DIP ; WITHOUT POST	1.70
MICRO USB 3.0 DIP(12.55MM)+2DIP ; WITHOUT POST	1.20
MICRO USB 3.0 DIP(12.55MM)+2DIP ; WITHOUT POST	0.85
MICRO USB 3.0 DIP(12.55MM)+2DIP ; WITHOUT POST	0.45



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X.' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: MICRO USB 3.0 插板12.55无卷边
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC06-USBD10-125
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱国夷	DATE : 2014-02-23	DRAW NO: HYC-USB16063009
			SHEET NO. 1 OF 1