




RECOMMENDED PCB LAYOUT
PCB THICKNESS 0.8mm
GENERAL TOLERANCE ± 0.05

NOTES:

1. CURRENT RATING:
3.0A MAX.
2. DIELECTRIC WITHSTAND VOLTAGE:
100VAC.
3. TEMPERATURE RANGE:
 $-30^{\circ}\text{C} \sim 85^{\circ}\text{C}$.
4. CONTACT RESISTANCE:
40 MILLIONHM MAX.
5. INSULATION RESISTANCE:
100 MEGOHMS MIN.
6. INSERTION FORCE :
5N~20N.
7. UNMATING FORCE:
8N~20N.
8. DURABILITY:
10,000 CYCLES.
9. ALL PRODUCTS COMPLY WITH RoHS
ENVIRONMENTAL REQUIREMENTS.
- 10: MARK "▼" AS THE FOCUS,
FIRST ITEM INSPECTION.
- 11: MARK "⊗" TO MEASURE DIMENSIONS
FOR FAI.

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
TX1+	TX1-	CC1	D+	D-	VBUS						GND
RX1+	RX1-		D-	D+	CC2	VBUS					GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1




TABLE:

P/N	INSERT MOLD	SHELL	Stainless Steel;T=0.15mm;	Ni:50u"Min
		LATCH	Stainless Steel;T=0.3mm;	Electroplated semi-nickel matte tin;50u"Min;
		EMC SPRING	Stainless Steel;T=0.10mm	-----
		CONTACT	Copper Alloy;T=0.15mm	Ni:50u"Min; Au:CONTACT AREA:1u", Solder AREA:Sn 50-100u"
		PLASTIC	LCP(G.F30%) BLACK.	-----
P/N	PART NAME	MATERIALS		FINISH



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X." $\pm 2^{\circ}$ X.X" $\pm 0.5^{\circ}$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: USB TYPE C 公座14P (7+7P) 铆合壳 Gen3.0立贴带接地 卡钩有防呆	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HYC678-USBC14-130	MOLD NO.
 UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HYC-2601071657	SHEET NO. 1 OF 1



备注:

1. 把上下载带送入载带机进行调整，然后将产品按照指定的方式摆入下载带中，开动卷带机进行卷装（每卷包500PCS），卷装完成后需用上带缠绕最少20CM；
2. 在卷装OK的每卷盘面的指定位置上贴上物料和RoHS标签装入纸箱内；每箱装10盘
3. 纸箱用封箱带将其封好，胶带要求工字型，不可遮住标签；
4. 如果客户对包装标签另有要求，请按客户要求作业；有未满之零数箱需用缓冲材料填充；
5. 上载带剥离力:0.2-1.2N；



深圳市华宇创精密电子有限公司

TOLERANCE:		DRAWN BY :	DATE :	PART NAME:	
X.X ±0.30		陈一鸣	2014-02-23	包装图	
X.XX ±0.25					
X.XXX ±0.15					
X.* ±2* X.* ±0.5*		CHECKED BY:	DATE :	PART NO.	
		马跃	2014-02-23	MOLD NO.	
UNIT: mm [inch]		APPROVED BY:	DATE :	DRAW NO:	
SCALE:1:1	SIZE: A4	邱敏	2014-02-23	SHEET NO.	1 OF 1