

PCB板

技术要求:

1. 特性阻抗 50Ω
2. 频率范围 0-3GHz
3. 接触电阻 内导体≤30mΩ  
外导体≤30mΩ
4. 绝缘电阻 ≥5000MΩ
5. 介质耐压 1500V电流0.5mA AC/1min
6. 分离力 5-25N
7. 外观: 无斑点 毛刺 划痕 表面光亮无脏污 无变形等

1	302B铜套	1	黄铜	镀镍
2	302-H29.2母针	1	黄铜	镀金
3	302铜座	1	黄铜	镀镍
4	302绝缘体1-全包-50	1	PTFE	
5	302绝缘体2	1	PTFE	
6	302绝缘体3	1	PTFE	
序号	名称	数量	材料	备注




深圳市华宇创精密电子有限公司

TOLERANCE:

X.X ±0.30  
X.XX ±0.25  
X.XXX ±0.15

X' ±2' X.X' ±0.5'



UNIT: mm [inch]

SCALE:1:1 SIZE: A4

DRAWN BY :

陈一鸣

DATE :

2014-02-23

PART NAME:

BNC-KWE

CHECKED BY:

马跃

DATE :

2014-02-23

PART NO.

HYC07-BNC660-2950

MOLD NO.

APPROVED BY:

邱敏

DATE :

2014-02-23

DRAW NO:

HYC-2603250951

SHEET NO.

1 OF 1