



RECOMMENDED PCB LAYOUT

特性:Specifications:

电器:Electrical:

- 接触阻抗:Contact Resistance 50 milliohms MAX
- 耐电压:Dielectric Withstanding Voltage: 100 V AC AT Sea Level
- 绝缘阻抗:Insulation Resistance: 100 MEGA ohms MIN

材料:Material:

- 塑胶:Housing:Hing Temperature Thermoplastics, UL 94V-0 耐高温塑胶
- 端子:Contact: Copper Alloy 铜合金
- 铁壳:Shell: Copper Alloy 铜合金
- 电镀:Finish: 端子:Contact: Plated Gold in Mating Area; Tin On Solder Talls 接触点镀金. 脚镀锡

铁壳:Shell:

- Nickel/ Plating 镀镍



深圳市华宇创精密电子有限公司

<b>TOLERANCE:</b> X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	<b>DRAWN BY :</b> 陈一鸣	<b>DATE :</b> 2014-02-23	<b>PART NAME:</b> MINI USB 5PIN AB□ SMT TYPE
	<b>CHECKED BY:</b> 马跃	<b>DATE :</b> 2014-02-23	<b>PART NO.</b> HYC65-USBC05-920
 <b>UNIT: mm [inch]</b> <b>SCALE:1:1 SIZE: A4</b>	<b>APPROVED BY:</b> 邱敏	<b>DATE :</b> 2014-02-23	<b>DRAW NO:</b> HYC-2606110948
			<b>SHEET NO.</b> 1 OF 1