



\square SMT AERA
 PCB LAYOUT
 TOL ± 0.05 MM

注解

1. 素材要求:
 - 1.1 胶芯: LCP E130i, 防火等级: UL94V-0, 颜色: 黑色;
 - 1.2 端子: C5191-1/2H, T=0.15MM
 - 1.3 接地片: C2680-H, T=0.20MM
2. 电镀要求:
 - 2.1 端子: 接触区镀金1~30U", 焊接区域镀锡100~120U", 全部区域电镀镍底50~80U".
 - 2.2 接地片: 电镀纯雾锡100U", 全部区域电镀镍底50U".
3. 电气性能要求:
 - 3.1 额定电流 1.0A, 额定电压 12V DC
 - 3.2 耐压交流电压最小250VAC.
 - 3.3 绝缘电阻最小1000M 欧姆.
 - 3.4 接触电阻最大50毫欧.
4. 环境性能要求:
 - 4.1 使用环境-25摄氏度~80摄氏度
 - 4.2 部件耐热焊接温度符合230摄氏度30~60秒, 260摄氏度10秒要求.
5. 耐久寿命: 5000次MIN.



深圳市华宇创精密电子有限公司

TOLERANCE: X.X ± 0.30 X.XX ± 0.25 X.XXX ± 0.15 X' $\pm 2'$ X.X' $\pm 0.5'$	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 2.5PH 3P 6.5H侧压电池座 6.8柱
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. HVC04-BB3P2565D-68
UNIT: mm [inch] SCALE: 1:1 SIZE: A4	APPROVED BY: 邱敏	DATE : 2014-02-23	DRAW NO: HVC-2606171516
			SHEET NO. 1 OF 1