



☐ SMT AERA
PCB LAYOUT
TOL ±0.05MM

注解

1. 素材要求:
 - 1.1 胶芯: LCP E130i, 防火等级: UL94V-0. 颜色: 黑色;
 - 1.2 端子: C5191-1/2H, T=0.15MM
 - 1.3 接地片: C2680-H, T=0.20MM
2. 电镀要求:
 - 2.1 端子: 接触区镀金1~30U", 焊接区域镀锡100~120U", 全部区域电镀镍底50~80U".
 - 2.2 接地片: 电镀纯雾锡100U", 全部区域电镀镍底50U".
3. 电气性能要求:
 - 3.1 额定电流 1.0A. 额定电压 12V DC
 - 3.2 耐压交流电压最小250VAC.
 - 3.3 绝缘电阻最小1000M 欧姆.
 - 3.4 接触电阻最大50 毫欧.
4. 环境性能要求:
 - 4.1 使用环境-25 摄氏度~80 摄氏度
 - 4.2 部件耐热焊接温度符合230 摄氏度30~60 秒, 260 摄氏度10 秒要求.
5. 耐久寿命: 5000 次MIN.



深圳市华宇创精密电子有限公司

| | | | |
|---|--------------------|----------------------|-------------------------------------|
| TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X' ±2' X.X' ±0.5' | DRAWN BY : 陈一鸣 | DATE : 2014-02-23 | PART NAME: 2.5PH 3P 6.5H侧压电池座 无柱 |
| | CHECKED BY: 马跃 | DATE : 2014-02-23 | PART NO. HYC03-BB3P2565 |
| UNIT: mm [inch] SCALE:1:1 SIZE: A4 | APPROVED BY: 邱敏 | DATE : 2014-02-23 | DRAW NO: HYC-2606171523 |
| | | | SHEET NO. 1 OF 1 |