




RECOMMENDED PCB LAYOUT  
TOL:(±0.05)

备注:

1. 胶芯材质:LCP BLACK UL94-V0
2. 端子材质:C5210-EH, 镀镍底30u", 触点镀金1u", 焊脚镀雾锡120u".
3. 固定片材质:SUS201-3/4H, 镀镍底30u", 整体镀雾锡120u".
4. 有标示 ▼ 的为QC及IPQC之检验重点
5. 有标示 ⊗ 的为FAI检验尺寸
6. 有标示 ⊠ 的为变更处记号

 <b>深圳市华宇创精密电子有限公司</b>			
<b>TOLERANCE:</b> X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	<b>DRAWN BY :</b> 陈一鸣	<b>DATE :</b> 2014-02-23	<b>PART NAME:</b> 3.0PH 6.0H 3P侧压电池座 3.0柱
	<b>CHECKED BY:</b> 马跃	<b>DATE :</b> 2014-02-23	<b>PART NO.</b> HVC02-BB3P3060D-30
 	<b>APPROVED BY:</b> 邱敏	<b>DATE :</b> 2014-02-23	<b>DRAW NO:</b> HVC-2606171532
<b>SCALE:1:1</b>	<b>SIZE: A4</b>	<b>SHEET NO.</b> 1 OF 1	